



APCL

Floodlight CICLO L



Compact circular floodlight. Comprehensive range available in three sizes with extensive optical and light distributions from 15W up to 75W to cover all applications. Can be tilted in all directions thanks to its fixing bracket. Ready for any intelligent lighting control solutions.

MAIN FEATURES:

- High efficiency. Up to 140 lm/W net
- 3 different sizes. From 15W to 75W
- 18 light distribution curves
- Zhaga Standard (Book 15)
- Tilting by means of a joint
- Several accessories for its fixing to a pole
- Optional RGBW with control DMX-514

APPLICATIONS:

- Bicycle Lanes and Narrow Roads
- Pedestrian Zones
- Commercial and Tourist Streets
- Squares
- Green Areas; Parks and Gardens
- Architectural; Buildings and Monuments

[Project sheet](#) | [CAD](#) | [Catalogue](#) | [HD image](#)


BENITO

info@benito.com
tel. 93 852 1000

SPECIFICATIONS :

Housing material:	High pressure die-cast aluminium EN AC-43000, EN AC-43100, EN AC-43400, EN AC-44100, EN AC-47100 according to the UNE EN 1706 standard
Diffuser (optic system enclosure):	5mm tempered safety glass. UV filter
Fixing elements:	Stainless steel 18/8 - AISI 304
Housing:	Double compartment: driver / LED module
Sealing gaskets:	Silicone foam
IP rating (luminaire):	IP66
IP rating (optic system):	IP66
IK rating (impact resistance):	IK08
LEDs thermal dissipation:	Thermal dissipation through finless luminaire body, without conductive fluids. Passive convection dissipation ensuring thermal contact with the LED modules through a high-conductivity thermal transfer material
Anti-condensation valve:	Pressure-balancing valve to ensure moisture release, avoid condensation and maintain the luminaire IP tightness
Paint and finishes:	Polyester powder paint coating, electrostatically sprayed and sublimated in the oven. Resistant to corrosion
Colour:	Microtextured black color and other colors upon request
Mounting:	Joint adaptable to clamp for simple or double pole, and TOP 60 mm
Tilt range:	From -60° to 60°
Maintenance:	Top opening. Modular concept for easy component replacement: LEDs, drivers, SPD
Recommended mounting height:	8-10 m
Driver:	Constant current adjustable and programmable driver. Embedded in the luminaire, pre-wired on a galvanised steel plate
Flow Reduction:	Dimmable driver 0-10V. Programmable on 5 levels. Optional: DALI 2. Includes the characteristics of Wireless, AOC, MTP, DTL
Ready4IoT - Connectivity:	- Autonomous multiple-level dimming or virtual midnight - Ready4IoT - Dimming by main voltage - Line switch
Surge protection device (SPD):	Type 2, 10kV and 20kA transient surge protector. Series connection with thermofuse disconnecter for a more effective protection at the end of its service life


DRAWING:



INSTALLATION:




V. 2024-05-15 | The constant improvement and evolution of our products may result in some modifications of the technical specifications and characteristics of the products without prior notice.




TECHNICAL DATA:

	REF.	N° LEDs	Power W	I Driver mA	Real luminous flux (T) =85°C)		Initial luminous flux (T) =25°C)	
					Flux lm	Efficacy lm/W	Flux lm	Efficacy lm/W
CICLO L	APCL75	28	30	322	3930	131	4440	148
		28	50	536	6500	130	7400	148
		28	70	750	8820	126	10010	143

Luminous flux and efficiency at 4000°K and CRI>70.
Luminous flux tolerance < +/-3%.
Values may be subject to changes due to LED binning.



PHOTOMETRY:



*Show 4 recommended lighting distributions. Refer to the 18 typologies.

V. 2024-05-15 | The constant improvement and evolution of our products may result in some modifications of the technical specifications and characteristics of the products without prior notice.

LEDs MODULE:

LEDs module:	BENITO-NOVATILU Zhaga standard for 8, 12 and 16 LEDs. Check colour temperature, CRI and light distributions	
Replaceable module:	Yes	
LED:	5050	
Number of LEDs:	28	
PCBs format:	2 Zhaga (Book 15) 2x4 + 1 Zhaga (Book 15) 2x8	
LED nominal efficacy:	172	
Colour temperature:	PC Amber, 2K2, 2K7, 3K, 4K, 5K, opTional RGBW	
Colour rendering index CRI:	>70 (optional >80)	
Average LED useful time L90B10:	L90B10 >100.000 horas	

OPTIC SPECIFICATIONS:

Optic system:	PMMA lenses 2x2	
Light distributions:	18 light distribution curves	
Upward light output ratio ULOR:	0%	
Downward light output ratio DLOR:	100%	
Glare index:	Between D5 and D6 (depending on the light distribution)	
Luminous intensity category:	Between G*4 and G*6 (depending on the light distribution)	
Luminous flux CIE n°3:	>95%	
Photobiological safety:	RG0 (exempt of risk)	
Initial luminous flux Tj=25°C (up to):	lm	10688
Initial luminaire efficacy Tj=25°C (up to):	lm/W	130
Real luminous flux Tj=85°C (UNE EN 13032-4) (up to):	lm	9375
Real luminaire efficacy Tj=85°C (UNE EN 13032-4) (up to):	lm/W	125

ELECTRIC SPECIFICATIONS:

Nominal maximum power (LEDs):	W	67,5
Maximum power consumed (luminaire):	W	75
Power range:	W	40W - 75W
Maximum current of LED:	mA	<400 (<50% I _{max})
Power supply protection classes IEC:	Class I and II	
Surge protection device (SPD):	Type 2, 10kV and 20kA transient surge protector. Series connection with thermofuse disconnecter for a more effective protection at the end of its service life	
Common and differential mode protection (SPD) Udc:	kV	10 y NTC opcional
Max current (8/20) (SPD):	kA	20
Thermal phase disconnection (SPD):	Yes	
Input voltage:	Vac	220-240
Input voltage (max rate):	Vac	198-264
Input frequency:	Hz	47-63
Starting current:	A	<65
Duration of the starting voltage peak:	ms	<0,3
Driver efficacy:	>90%	
Power factor 100% consumption:	>0,98	
Power factor 50% consumption:	>0,95	
Total harmonic distortion (THD):	<10	
Power consumption on standby mode:	W	<0,4
Energy class:	A++ IPEA>1,15	

OPERATING CONDITIONS:

Average LED useful time L90B10:	hours	100.000
Average driver useful life to Tp <70°C:	hours	100.000
Average luminaire useful life L90B10 (TM-21):	hours	96.000
Ambient temperature (Ta):	°C	de -35°C a +50°C
Aerodynamic resistance (CxS):	m2	0,09
Vibration test (15Hz 3 axis):		
Guarantee:	years	5 years (extensible up to 10 years)

PACKAGING DIMENSIONS:

Net weight	kg	5,3
Gross weight	kg	
Luminaire dimensions (LxWxH)	mm	Ø 268 mm x 272 mm
Packaging dimensions (LxWxH)	mm	
Pieces per box		1
Quantity per container 20ft		
Quantity per container 40ft		

CERTIFICATES:

Security certificates:	EN 60598-1 / EN 60598-2-5 / EN 62493 / IEC 62471
EMC certificates:	EN 55015 / EN 61547 / EN 61000-3-2 / EN 61000-3-3 / EN 61347-2-13 / EN 61347-1 / EN 62384
Other certifications:	IEC 62262 / EN 13032-4 / EN 62717 / EN 6272-1 / EN 6272-2-1 / EN 61643-11

Company Certifications



V. 2024-05-15 | The constant improvement and evolution of our products may result in some modifications of the technical specifications and characteristics of the products without prior notice.